


Breaks Up Sludge in Drain Fields

Septic Blaster

Restores Output in Failing Drain Fields

Blasts Out Blockages

Breaks Down Fats, Oils, & Greases




- A. Water from House Flows into Septic Tank
- B. F.O.G. Floats on Water (Fats, Oils, & Grease)
- C. Water in Septic Tank
- D. Sludge in the Septic Tank
- E. Water & F.O.G. Exits Septic Tank to Drain Field

Directions: To clean drain fields add 4-8 lbs. of Septic Blaster directly to distribution box, septic tank, or flush down kitchen sink or toilet. Flush with water from shower, washing machine, dishwasher, or flush toilets repeatedly. This forces the water and Septic Blaster to enter the drain field quicker. If drain field still is very heavily blocked, add another 4-8 lbs. after 2-3 weeks. To keep it clean, add 4

- 4 x lb. Containers
- 2 x 25 lb. Containers
- 1 x 50 lb. Pail

Septic Blaster Starts Working on Contact and Keeps Working For Several Weeks



Holes Allow F.O.G. to Enter Drain Field F.O.G. Collects Solids & Paper and Clogs Drain Field

Never Pump Your Tank Again!



Fats, Grease & Oils Acts Like Glue to Trap Waste Solids & Paper Causing Sludge to Form Forms Coating in & Below Drain Field Pipes Coating Prevents Water from Seeping into Ground Waste is Pushed up to Surface, Drain Field Clogged



CAUTION:
KEEP OUT OF REACH OF CHILDREN

INGESTION: Give 8 to 16 ounces of water to dilute substance. Call a physician or local Poison Control Center immediately. Never give anything by mouth to an unconscious person.
EYES: Flush eyes with water for at least 15 minutes. If irritation persists, call a physician.
SKIN: If skin becomes irritated, rinse with water.
INHALATION: Product is dusty. Do not breathe in dust. If symptoms of over exposure develop, remove to fresh air.

Line Blaster, Inc
info@septicblaster.com
800-CHEM-911
www.septicblaster.com


Breaks Up Sludge in Drain Fields

Septic Blaster

Restores Output in Failing Drain Fields

Blasts Out Blockages

Breaks Down Fats, Oils, & Greases




- A. Water from House Flows into Septic Tank
- B. F.O.G. Floats on Water (Fats, Oils, & Grease)
- C. Water in Septic Tank
- D. Sludge in the Septic Tank
- E. Water & F.O.G. Exits Septic Tank to Drain Field

Directions: To clean drain fields add 4-8 lbs. of Septic Blaster directly to distribution box, septic tank, or flush down kitchen sink or toilet. Flush with water from shower, washing machine, dishwasher, or flush toilets repeatedly. This forces the water and Septic Blaster to enter the drain field quicker. If drain field still is very heavily blocked, add another 4-8 lbs. after 2-3 weeks. To keep it clean, add 4

- 4 x lb. Containers
- 2 x 25 lb. Containers
- 1 x 50 lb. Pail

Septic Blaster Starts Working on Contact and Keeps Working For Several Weeks



Holes Allow F.O.G. to Enter Drain Field F.O.G. Collects Solids & Paper and Clogs Drain Field

Never Pump Your Tank Again!



Fats, Grease & Oils Acts Like Glue to Trap Waste Solids & Paper Causing Sludge to Form Forms Coating in & Below Drain Field Pipes Coating Prevents Water from Seeping into Ground Waste is Pushed up to Surface, Drain Field Clogged



CAUTION:
KEEP OUT OF REACH OF CHILDREN

INGESTION: Give 8 to 16 ounces of water to dilute substance. Call a physician or local Poison Control Center immediately. Never give anything by mouth to an unconscious person.
EYES: Flush eyes with water for at least 15 minutes. If irritation persists, call a physician.
SKIN: If skin becomes irritated, rinse with water.
INHALATION: Product is dusty. Do not breathe in dust. If symptoms of over exposure develop, remove to fresh air.

Line Blaster, Inc
info@septicblaster.com
800-CHEM-911
www.septicblaster.com